

Product Profile

RUS Deep drill with air leg

The Deep drill is pneumatic hand-held drilling bolter. It is safety explosion-proof, large torque, high speed, light weight, small size, high efficiency, simple structure, convenient maintenance, etc.,

Suitable for detecting geological structure coal seams, exploration and release water, drainage tiles, water injection, coal discharge pressure, drilling through roadway from the front hole, roadway anchor support hole and other special purposes. Therefore, the rig is a very necessary emergency equipment for coal mine safety production.

SPECIFICATIONS

Air pressure(psi)	58	72	91
Torque Rate(N.m)	60	80	85
Rotate speed(r/min)	315	335	340
Max. Output power(kW)	2	2.8	3
Max. load torque(N.m)	95	115	130
Power starting torque(N.m)	105	125	135
Dynamic stall torque(N.m)	110	130	140
Air consumption(m ³ /min)	3	3.5	4
No-load speed (r/min)	800	950	1000
Machine weight	12kg		
Water pressure	100-175psi		
Water flow	20 L/min		
Air hose size	25mm		
Drill chuck	25mmSQ		
Housing material	stainless steel		



Contact

Head Office: 5 Montore Road, Minto, NSW 2566 Australia.
Postal Address: PO Box 322, Minto, NSW 2566
Phone: (02) 8796 9800
Fax: (02) 9824 8158
Email: Russales@rusmining.com.au