

Product Profile

Longwall Temporary Support



General Specifications

Specifications	DW22-30/100B	DW25-30/100B	DW28-30/100B
Max.Height (mm)	2240	2500	2800
Working Stroke(mm)	570	570	570/820
Rated Resistance(kN)	30	30	30
Rated Working Pressure(Mpa)	3.8	3.8	3.8
Supporting Force(kN)	30	30	30
Cylinder Inside Dia.(mm)	Ø 100	Ø 100	Ø 100
Relief Pressure(Mpa)	3.8	3.8	3.8
Weight(kg)	21	21.8	22.5/28.5
Applicable medium	Emulsion Liquid(Including 2% M-10 emulsion oil), Static Pressure Water		

General Specifications

Specifications	DW31.5-30/100B	DW35-30/100B	DW38-30/100B
Max.Height (mm)	3150	3500	3800
Working Stroke(mm)	570	570	820
Rated Resistance(kN)	30	30	30
Rated Working Pressure(Mpa)	3.8	3.8	3.8
Supporting Force(kN)	30	30	30
Cylinder Inside Dia.(mm)	Ø 100	Ø 100	Ø 100
Relief Pressure(Mpa)	3.8	3.8	3.8
Weight(kg)	25	27	36
Applicable medium	Emulsion Liquid(Including 2% M-10 emulsion oil), Static Pressure Water		

Contact

Head Office: 5 Montore Road, Minto, NSW 2566 Australia.

Postal Address: PO Box 322, Minto, NSW 2566

Phone: (02) 8796 9800

Fax: (02) 9824 8158

Email: Russales@rusmining.com.au